

publications describe the corresponding method. All previous patents relate to regular 2D or 3D images and disclose formation of 2D or 3D surface images (without any internal structure) inside transparent materials.

The foundation for the production of an image with visible internal structure is the creation of the special arrangement of laser-induced damages reproducing the internal structure. The first step of this action is producing an arrangement which has damage density corresponding to the density of internal structure so that distances between adjacent damages are larger than minimal critical value. However, if this damage arrangement is produced, usually, internal structure is not visible (or badly visible). Therefore, it is necessary to make the following step which is modification of the first arrangement so that internal structure becomes visible. This modification is produced by the moving away of separate damages. This action disturbs the correlation between the density of the damages and the density of the internal structure. However, for a viewer (researcher) it is important to preserve visual internal effect. Correction of the visual internal picture is produced so that its gray shades correlate with gray shades of the first damage arrangement. It can be made by changing the brightness of separate damages (so-called “differential” method).

Another way of the right visualization of internal structure is transformation of an internal structure of an image into an aggregate of several images enclosed in each other and the modification of these images into multi-surface arrangement. It is so-called “integral method”, which also replaces the reproduction of internal density structure by corresponding gray shades so that internal structure is visible. In this method, the visualization is provided by the redistribution of the damages (but not moving away) and so to reproduce the right gray shades.

Figures 1-3 illustrate simple art laser-induced images produced by the disclosed methods. It is also very important that the methods can be used for visualization of tomography images, which are typical images with complicated internal structures. In tomography there are two processes: at the beginning, internal structure is represented as an aggregate of 2D separate images and after the reconstruction of these 2D images from tomography data, the inverse task is decided – the reconstruction of 3D internal structure from these 2D images. Theoretical research of these processes is published (for example,

in monograph "Statistical Theory of Tomography", Igor Troitski, Moscow, Radio and Communication, 1989; "Statistical Simulation of Tomographic Images" I. Troitski et al., Allerton Press, Inc, 1987; "Analysis of an Algorithm for Approximating Tomographic Projections" to I. Troitski et al. Allerton Press, Inc, 1987; copy of the articles are enclosed). Methods disclosed in the present invention provide realization of the theoretical algorithms and in practice permit to see internal structure not as aggregate of 2D reconstructed images but as the united internal structure. It is very important to notice, that for visualization of tomography internal structure it is necessary to use multi-layer arrangement and also to move away the damages which shade the internal damages along the direction perpendicular to axis Z. The number of the layers is determined by value of normalization parameter used in the tomography reconstruction process and the distances between adjacent layers should be larger than the minimal critical value characteristic for the transparent material.

Claim 18 (New, independent) discloses a method for visualization of internal structure by moving away separate damages and compensation of the visual effect by the changing brightness of other separate damages.

Claim 22 (New, independent) discloses a method for visualization of internal structure by the transformation of an internal structure of an image into an aggregate of several images enclosed in each other and modification of these images into multi-surface arrangement without modulation of the brightness of the separate damages.

Claim 22 (New, independent) discloses a method for visualization of internal structure of tomography images by transformation of reconstructed tomography images into multi-layer arrangement of damages so that one tomography layer image is visible through another.

Summary

Applicants assert that new claims 18 - 27 are in a condition for allowance and respectfully request a notice as to the same.

Igor Troitski

/s/ [Signature] 6/2/08/05

DESCRIPTION OF THE DRAWINGS

Figure 1 shows the laser-induced image of an egg containing a 3D church image. Here the 3D church is the internal structure of the laser-induced image. Visualization of the internal structure is produced by moving away the outer damages which shade the internal damages.

Figure 2 shows the laser-induced image of a balloon containing a 2D portrait. Here the 2D portrait is the internal structure of the laser-induced image. Visualization of the internal structure is provided by using a special multi-surface arrangement of laser-induced damages.

Figure 3 shows the laser-induced image of a golf ball containing a 3D portrait. Here the internal structure of the laser-induced image is the 3D portrait. Visualization of the internal structure is provided by moving away the outer damages which shade the internal damages and by using a special multi-surface arrangement of laser-induced damages.

/Ravi 02/02/25